

# Nexus 990 Carpet Latex

## TECHNICAL DATA SHEET

### DESCRIPTION

**Nexus 990 Carpet Latex** is a Natural Latex compound for sealing raw edges of carpet and installing felt underlay to substrates.

### METHOD OF APPLICATION

Prior to joining carpet seams with heat bond tape or seam sealer, apply **Nexus 990** to edge of carpet and allow drying.

Doing this helps prevent with loss of tufts and unraveling after seams have been trimmed.

When used to install felt underlay to subfloors apply a liberal amount to the subfloor and install underlay into wet latex.

### CLEAN UP

Clean tools immediately after use with warm soapy water.

### Typical Properties

Base:	Natural Latex
Appearance:	White Liquid
Viscosity:	Thin Liquid
Shelf Life:	12 months in sealed container at 20°C
Packaging:	1, 4 & 15 Litre
Odour:	Ammonia
Freezability:	Avoid Freezing

**Note:** Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

October 2013

**Nexus Adhesives Pty Ltd**

ABN 61 121 120 036

42 Healey Road  
Dandenong South VIC 3175 Australia

**Tel** +61 3 9706 4022

**Fax** +61 3 9706 4122

info@nexusadhesives.com.au

www.nexusadhesives.com.au